

## INC4335M – 2MP SMART Weatherproof IR Camera



**2MP** **60fps**

**H.264+** **50m IR**

**2.8-12mm Motorized** **Tri-Stream**

**WDR** **IP67** **uSD** **POE**

### Features

- Up to 1920x1080 @60fps
- H.264+ Compression
- 2.8-12mm Motorized Zoom Lens
- Optional 8-32mm
- 3D-DNR, DSS, Defog, ROI, BLC, HLC
- 140dB True WDR
- Day&Night by Filter Change (TDN)
- 0 Lux up to 50m, Smart IR
- uSD slot up to 128GB, IP67
- Smart : **Face Recognition, Intrusion, Line Crossing, Object left/removal/Counting, Area Enter/Leave, Scene Change, Audio Surge/Loss, Defocus**
- 20ch live view

### SPECIFICATION

Model	INC-4335M
Image Sensor	1/2.8" progressive scan CMOS Sensor
Resolution	1920x1080 @60fps
Shuttle	1s ~ 1/100,000s
Lens	2.8~12mm F1.4 Motorized Zoom Lens with Auto Focus
Others Connection	Video Composite Out
Minimum Illumination	0 Lux up to 50m
Network	10/100/1000-BaseT RS45
Compression	Tri-Stream : H.264+ / H.264 / MJPEG
ONVIF	Profile S, Profile G
Working Environment	-30° ~ +60°C, <90° Humidity (Non-Condensing)
Power	POE IEEE 802.3at compliant, or 12VDC, Max. 12W (IR-On)
Dimension	100mm x 104mm x 312mm(L), 2kg

\* Specification maybe changed without prior notice