

CNC3510A – 4M POE IR Dome with Build-in Mic



Features

- 4 Megapixel 2688x1520 @25fps
- **H.265** Compression
- ONVIF compatible
- **2.8/3.6mm** Fixed Lens
- 3D-DNR, **120dB True WDR**, DSS, HLC, Defog, etc
- 8x ROI, 3-Stream, TDN, CVBs out
- uSD Slot up to 128GB
- 0 Lux up to 5m
- Build-in Mic. + Mic. In
- Network 10/100 Base-T
- POE / 12VC Dual Power
- Vandal Resistant

SPECIFICATION

Model	CNC3510A
Image Sensor	1/2.7" progressive scan CMOS Sensor
Resolution	4MP 2688x1520 @25fps (PAL)
Shuttle	1/25s ~ 1/100,000s
Lens	M12 2.8 or 3.6mm Fixed Lens
LEDs	2nos 850nm IR LED Array
Day & Night	Filter Change or TDN (True Day & Night)
Min. Illumination	0 Lux up to 5m
Network	10/100-BaseT, RJ45
Bit Rate	128Kbps ~ 6Mbps
Compression	3-Stream : H.265 / H.264 / MJPEG
W. Environment	-20°~+50°C, <90% Humidity (Non-Condensing)
Power	POE IEEE 802.3af /12VDC, Max. 4.5W
Dimension	110mm(φ) x 58mm(H), 300g

