

## CNC4660 – 6M POE Fisheye Camera



### Features

- 6 Megapixel 3072x2048 @25fps
- H.264 High Profile
- ONVIF compatible
- 1.05mm 180° Fisheye Lens
- 3D-DNR, Dual Stream
- Day&Night by Filter Change (TDN)
- LED Array, 0 Lux up to 15m
- Build-in Audio Mic, Audio In/Out
- 1 Alarm In / 1 Alarm Out
- uSD Card storage up to 64GB
- IE, Firefox, Chrome support
- Android, iPhone/iPad application
- 64ch CMS Software included

### SPECIFICATION

Model	CNC4660
Image Sensor	1/2" progressive scan CMOS Sensor
Resolution	1x Fisheye 3072x2048@25fps or 4x PTZ 1024x768@25fps
Multi Channel	1x Fisheye 1280x1280@15fps, 1x Panoramic 2048x1536@15fps & 3xPTZ 1024x768@15fps
Shuttle	1/25s ~ 1/100,000s
Lens	1.05mm 180° Fisheye Lens
LEDs	3nos 3W 850nm IR LED Array
Day & Night	Filter Change or TDN (True Day & Night)
Minimum Illumination	0 Lux up to 15m
Network	10/100-BaseT, RJ45
Working Environment	-30° ~ +60°C, <90° Humidity (Non-Condensing)
Power	POE IEEE 802.3af compliant, or 12VDC, Max. 12W (IR-On)
Dimension	140mm(φ) x 114mm(H), 1.4kg

\* Specification maybe changed without prior notice