

CNC4312M – 2M POE IR IP Motorized Dome



Features

- Up to 2 Megapixel @25fps
- H.264 High Profile
- ONVIF compatible
- **2.7-12mm Motorized Zoom&Focus Lens**
- 3D-DNR, ROI, Dual Stream, DWDR, DSS, BLC
- Day&Night by Filter Change (TDN)
- 20 IR LEDs, 0 Lux up to 20m
- SMART-IR
- Build-In SD Card Slot up to 128GB
- Vandal Resistant
- Smart : Line Crossing & Intrusion

2 Mega

Motorized Lens

20m IR

uSD

POE

ONVIF

SPECIFICATION

Model	CNC-4312M
Image Sensor	1/2.7" progressive scan CMOS Sensor
Resolution	50Hz 1920x1080 @25fps
Shuttle	1/3s ~ 1/100,000s
Lens	2.7~12mm (113°~33.8°) Motorized Varifocal Lens
LEDs	20nos φ5 850nm IR LED
Day & Night	Filter Change or TDN (True Day & Night)
Minimum Illumination	0 Lux up to 20m
Network	10/100-BaseT, RJ45
Bit Rate	32Kbps ~ 16Mbps
Compression	Dual Stream : H.264 High Profile / MJPEG
Working Environment	-10° ~ +60°C, <90° Humidity (Non-Condensing)
Power	POE IEEE 802.3af compliant, or 12VDC, Max. 5.5W (IR-On)
Dimension	140mm(φ) x 100mm(H), 1kg

* Specification maybe changed without prior notice