



CNC4561 – 5M POE Fisheye Camera



Features

- **5 Megapixel** 2560x1440 @25fps
- **H.265+**/H264+, ONVIF compatible
- 1.16mm 180° Fisheye Lens
- 3D-DNR, Dual Stream
- Wall / Ceiling / Desktop mode
- LED Array, 0 Lux up to 8m
- **Build-in Mic**
- **Audio** 1 In/1 Out
- **Alarm** 1 In / 1 Out
- **uSD** Card storage up to 128GB
- Alarm Trigger : Line Crossing, Intrusion, Motion Dection, Unattended baggage, Object removal, Face Detection etc

SPECIFICATION



Unit: mm

Model	CNC4561
Image Sensor	1/2.5" progressive scan CMOS Sensor
Resolution	2560x1920@20fps or 2560x1440@25fps
Shuttle	1/3s ~ 1/100,000s
Lens	1.18mm 180° Fisheye Lens
LEDs	1nos 3W 850nm IR LED Array
Day & Night	Filter Change or TDN (True Day & Night)
Min. illumination	0 Lux up to 8m
Network	10/100-BaseT, RJ45
Security	User Authentication, Address Filtering
Working Environment	-10° ~ +40°C, <90° Humidity (Non-Condensing)
Power	POE (802.3af)/12VDC, Max. 5.55W (IR-On)
Dimension	120mm(φ) x 41.2mm(H), 0.6kg