

Model: Snowman Series
Product Features

- ◆ Easy installation and use, plug and play
- ◆ View the video anytime and anywhere. Support multiple platforms, terminals, networks
- ◆ Clear and smooth video, intelligent transmission
- ◆ Bank level security control and ensure privacy
- ◆ Online firmware upgrade, update function and experience synchronously
- ◆ H.264 video compression, transmit HD video in narrow bandwidth. High picture quality, low bit stream, local HD video recording. Watch more smoothly and no streaking
- ◆ Support two-way audio, telecommunication level of signal processing, (echo cancellation, noise suppression, comfort noise, silence suppression)
- ◆ Support Android /iOS system mobile devices, remote real-time monitoring
- ◆ Motion detection, linkage snapshot/video recording, real-time App push notifications
- ◆ Infrared night vision lighting(IR distance: 10 meters), 24 hours day and night monitoring, IR-CUT switch
- ◆ Support micro SD card (max 64GB) storage, cloud box and cloud storage
- ◆ Support QR code login
- ◆ Support digital zoom


Specifications
CP2
CP2-X

Specifications		CP2	CP2-X
Image sensor	Image sensor	1/4 "color CMOS sensor	1/2.7"color CMOS sensor
	Display resolution	1280*720 (1mega pixels)	1920*1080(2Mega pixels)
	Lens	f: 3.6mm, 1mega pixels	f: 3.6mm, 2mega pixels
	Visual angle	H:60.5°; V:37°; D:72°	H:80°; V:65°; D:100°
Minimum illumination		0.1Lux(IR LED OFF)	
Audio	Input/output	Built-in microphone and speaker	
	Audio compression	AAC	
Video	Video compression	H.264	
	Lighting frequency	50Hz, 60Hz	
	Image frame rate	25fps	
	Image resolution	1280*720(1.0Mega Pixels)	1920*1080(2.0Mega Pixels)
	Image adjustment	Brightness, Contrast, Saturation, Sharpness	
White balance, BLC		Automatically	
Night vision		1 pcs matrix infrared lights, IR distance: 10 meters	
Internet	Wireless networks	WIFI(IEEE802.12b/g/n),internal antenna	
	Ethernet	10/100Mbps	
	Protocols	TCP/IP、UDP/IP、HTTP、DHCP、RTMP、MUTP	
	IP address	Static IP address and dynamic IP address	
RF	Support connecting RF	/	
Intelligence	Face detection	/	
POE	POE	/	
Pan&Tilt	Pan&Tilt	Horizontal:350°& Vertical:90°	
Alarm	Alarm detection	Motion detection	
	Alarm linkage	Snapshot, audio/video record	
	Alarm notification	Real-time App push notifications	
	RF Peripheral	/	
Interface	power	1DC 5V / 2.0 A,USB interface, power consumption < 7W	
	Buttons	A reset hole, a FN button	
	Network interface	RJ45	
Others	Adjustable lens	No	
	LED instructions	Network signal/network function	
	Video storage	Micro SD(maximum 64GB),cloud box, cloud storage	
Environment	Work temperature	0° ~ 55°C (32°F ~ 131°F)	
	Work humidity	10% ~ 80% (No condensation)	
	Storage temperature	-10°C ~ 60° (14°F ~ 140°F)	
	Storage humidity	0% ~ 90%(No condensation)	
Color	Color	White and black	
Specifications	Size(L*W*H)	85(L)X85(W)x120(H)mm	
	Weight	267g (not include rack)	
Certification	Certificate	RoHS, CE, FCC, NCC	