

## CNC-3611-S – 5MP WDR SMART IR IP Dome Camera



### Features

- **5 Megapixel** 2592x1944 @20fps
- **H.265+** Compression
- ONVIF compatible
- 3.6mm Fixed Lens
- 3D-DNR, DSS, HLC, Defog, etc
- 3x ROI, 3-Stream
- 140dB True **WDR**
- Network 10/100 Base-T
- POE / 12VC Dual Power
- Smart Functions : **Object Removal, Abnormal Video, Line Crossing, Region Intrusion, People Counting, Crowd Density, Face Recognition**

### SPECIFICATION

Model	CNC-3611-S
Image Sensor	1/1.8" progressive scan CMOS Sensor
Resolution	5MP 2592x1944 @20fps 4MP / 3MP / 2MP / 720p @25fps
Shuttle	1/25s ~ 1/100,000s
Lens	M12 3.6mm Fixed Lens
LEDs	30nos Φ4 850nm IR LED
Day & Night	Filter Change or TDN (True Day & Night)
Min. Illumination	0 Lux up to 20m
Network	10/100-BaseT, RJ45
Bit Rate	128Kbps ~ 6Mbps
Compression	3-Stream : H.265+ / H.264+
Working Environment	-20° ~ +50°C, <90° Humidity (Non-Condensing)
Power	POE IEEE 802.3af compliant/12VDC, <6.5W
Dimension	87mm(φ) x 108mm(H), 430g

