


N5-3216-5ML-V2 – 16ch 5MP-Lite H.265+ DVR



Features :

- **H.265+** Compression – saving 50% HDD space
- Stable & Economical Linux base
- 16 Individual channel auto detect :
 - **Analog** (960H) @Real-time 25fps
 - **AHD / TVI 720p** @Real-Time 25fps
 - **AHD / TVI 1080p** @Real-Time 25fps
 - **5MP** @20fps
- Support **8ch IP Cameras** up to **5MP**
- 1080p HDMI & VGA & CVBs output
- **UTC** Camera OSD Control
- **Audio : 8 In / 1 Out**
- **Alarm : 16 In / 4 Out**
- **16ch** Simultaneous Playback
- Support 2HDD (Max. 10TB each)
- eSATA x1 for backup
- Max. **10** users simultaneous login

SPECIFICATION

Model	N5-3216-5ML-V2
Channel	16 Analog + 8 IP Cameras (up to 5MP)
Recording	WD1(960x676), 1080-Lite(960x1080)@25fps/ch 1080p(1920x1080)@12fps / 5MP-Lite(1296x1944)@10fps/ch
Video Out	1x 1080p VGA, 1x 1080p HDMI, 1 CVBs out
Alarm	16 Alarm In / 4 Alarm out
Audio	8ch Audio in / 1ch Audio out
Network	10/100/1000 self adaptive RJ45 Ethernet port
Bandwidth	32Mbps Incoming / 96Mbps Outgoing
Working Environment	-10° ~ +50°C, 10~90% Humidity
Power	12VDC, <15W w/o HDD (4A Adapter Included)
Dimension	380 x 268 x 45mm, 3.6kg w/o HDD