




Name: New Waterproof Cloud IP Camera		Product Features:		
		◆ Easy operation, plug and play		
		◆ Clear, Smooth video viewing		
		◆ Dynamic encryption to protect privacy		
		◆ Support remote firmware upgrade		
		◆ H.264 video compression algorithm, Smart transmission technology, adaptive bandwidth, dynamic code rate adjustment, voice		
		◆ Support Android /iOS system mobile devices remote monitoring		
		◆ Motion detection, Real-time App push notifications		
		◆ Infrared LEDs night vision distance: 20 meters, 24 hours day and night monitoring, IR-CUT switch		
		◆ Support 2.4G WIFI(IEEE802.11b/g/n)		
		◆ Support uSD and NVR storage		
◆ Support QR code login				
◆ External SD card slot, easy to install				
Specifications		B3-C	B3-S	
Image sensor	Image sensor	1/4"color CMOS sensor	1/2.7"color CMOS sensor	
	Display resolution	1280*720 (720P)	1920*1080 (1080P)	
	Lens	f: 3.6mm 960P	f:3.6mm, 1080P	
	Vision Angle	H60.5°; V34°; D70°	H80°; V45°; D92°	
	Min. illumination	0.01Lux		
Audio compression		AAC		
Video	Video compression	H.264		
	Image frame rate	25fps		
	Image resolution	1MP	2MP	
	Image adjustment	Brightness, Contrast ratio, Color Saturation, Sharpness		
	White balance, BLC	Automatically		
	Night vision	36infrared LEDs (14MIL,850nm),IR distance: 20 meters		
	Wireless networks		2.4G WIFI(IEEE802.11b/g/n), external 3DB antenna	
Internet	Ethernet	10/100Mbps		
	Protocols	TCP/IP、UDP/IP、HTTP、DHCP、RTMP、MUTP		
	IP address	Static IP address & Dynamic IP address		
	Alarm detection		Motion detection	
Alarm	Alarm linkage	Snapshot, audio/video record		
	Alarm notification	Real-time App push notifications		
	Power		1 DC 12V / 1A (Adapters UK Standard), power consumption < 10W	
Interface	Buttons	One reset button		
	Network interface	RJ-45 interface		
	IP Level		IP66 Waterproof	
Others	Video storage	Micro SD Card (Max.128G), Network Video Recorder		
	Work temperature		-10° ~ 55°C (14°F ~ 131°F)	
Environment	Work humidity		10% ~ 80% (No condensation)	
	Size(L*W*H)		196mm(L)×63mm(M)×63mm(H)	
Specifications	Weight		374g	
	Certification		RoHS,CE,FCC,NCC	