


CNC-3611 – 5MP IR IP Dome Camera



Features

- **5 Megapixel** 2592x1944 @20fps
- **H.265+** Compression
- ONVIF compatible
- 3.6mm Fixed Lens
- DWDR, 3D-DNR, DSS etc
- 3x ROI
- 3-Stream
- Day&Night by Filter Change
- 30nos IR LED
- 0 Lux up to 15m
- Network 10/100 Base-T
- POE / 12VC Dual Power

SPECIFICATION

Model	CNC-3611
Image Sensor	1/2.7" progressive scan CMOS Sensor
Resolution	5MP 2592x1944 @20fps 4MP / 3MP / 2MP / 720p @25fps
Shuttle	1/25s ~ 1/100,000s
Lens	M12 3.6mm Fixed Lens
LEDs	30nos Φ 4 850nm IR LED
Day & Night	Filter Change or TDN (True Day & Night)
Min. Illumination	0 Lux up to 15m
Network	10/100-BaseT, RJ45
Bit Rate	128Kbps ~ 6Mbps
Compression	3-Stream : H.265+ / H.264+
Working Environment	-20° ~ +50°C, <90° Humidity (Non-Condensing)
Power	POE IEEE 802.3af compliant/12VDC, <6.5W
Dimension	87mm(ϕ) x 108mm(H), 430g

