

Model:VT362 series



Product Features:

- · Easy installation and use, plug and play
- View the video anytime and anywhere, Support multiple platforms, terminals, networks
- Clear and smooth video, intelligent transmission
- ◆ Bank level security control and ensure privacy
- Online firmware upgrade, update function and experience synchronously
- H.264 video compression, transmit HD video in narrow bandwidth. High picture quality, low bit stream, local HD video recording. Watch more smoothly and no streaking ps: 3mp adopts Smart H.264 video compress algorithm, leads lower video bit rates and save space when recording.
- Support two-way audio, telecommunication level of signal processing, (echo cancellation, noise suppression, comfort noise, silence suppression)
- Support Android /iOS system mobile devices, remote real-time monitoring
- Motion detection, linkage snapshot/video recording, real-time App push notifications
- Infrared night vision lighting(IR distance: 6 meters),24 hours day and night monitoring, IR-CUT switch
- Support micro SD card (max 128 GB) storage, cloud box and cloud storage
- Support QR code login
- Support ditial zoom
- Support 2.4G WIFI(IEEE802.11b/g/n)
- ◆ Support P/T/Z remotely (Horizontal:350°& Vertical:100°)

			vertical.100°)	
Specifications		1MP	2MP	ЗМР
Image sensor	Image sensor	1/4 "color CMOS sensor	1/2.7"color CMOS sensor	1/3"color CMOS sensor
	Display resolution	1280*720 (1MP)	1920*1080 (2MP)	2304*1536 (3.5MP)
	Lens	f: 3.6mm, 1.3MP	f: 3.6mm, 2MP	f: 3.6mm, 3MP
	Visual angle	H:60.5°; V:34°; D:70°	H:80°; V:45°; D:92°	H:58°; V:41°; D:83°
	Minimum illumination	0.01Lux		
Audio	Input/output	Built-in microphone (-36dB) and speaker (8 Ω /1W),support two way audio		
	Audio compression	AAC		
Video	Video compression	H.264	H.264	Smart h.264
	Lighting frequency	50Hz, 60Hz		
	Image frame rate	Max 30fps		
	Image resolution	1MP	2MP	3MP
	Image adjustment	Brightness, Contrast, Saturation, Sharpness		
	White balance, BLC	Automatically		
	Night vision	1 Dot Matrix Infrared lights, IR distance: 6 meters		
Internet	Wireless networks	2.4G WIFI(IEEE802.11b/g/n),Built in PCB board 2DB antenna		
	Ethernet	10/100Mbps		
	Protocols	TCP/IP、UDP/IP、HTTP、DHCP、RTMP、MUTP		
	IP address	Static IP address and dynamic IP address		
Pan&Tilt	Pan&Tilt	Horizontal:350°& Vertical:100°		
Alarm	Alarm detection	Motion detection		
	Alarm linkage	Snapshot, audio/video record		
	Alarm notification	Real-time App push notifications		
	RF Peripheral	Work only with a RF connector		
Interface	Power	DC 5V MICRO USB (Europe, UK, USA type for option) power consumption < 8W		
	Buttons	A reset button		
	Network interface	RJ45		
Others	Adjustable lens	No		
	LED instructions	No		
	Video storage	Micro SD(Max128GB),cloud box, cloud storage		
Environme nt	Work temperature	-10° ~ 55°C (14°F ~ 131°F)		
	Work humidity	10% ~ 80% (No condensation)		
	Storage temperature	-10°C ~ 60° (14°F ~ 140°F)		
	Storage humidity	0% ~ 90%(No condensation)		
Color	Color	Black&Silver		
Specificatio	Size(L*W*H)	85(L)X85(W)x120(H)mm		
ns	Weight	267g (not include bracket)		
Certificatio	Certificate	RoHS,CE,FCC,NCC		