

## Ruijie AP710



### Product Features

- Maximize ROI (Cloud Management & Big Data Optimization Service)
- Fast Provisioning by Ruijie Cloud Mobile APP
- Automated Radio Optimization by Big Data Technology
- Scenario-based AP Options (Ceiling / Wallmount)
- Stylish Design (Integrated Antenna and Hidden Cabling)
- 3-Year Hardware Warranty

Model	Ruijie AP710
Target Deployment	Retail Chain Store, Small & Medium-sized Business Office, Boutique Hotel
Type	Indoor Ceiling/Wall-mounting
Radio	Concurrent Dual-band
Operating Bands	802.11a/n/ac: 5.150GHz to 5.350GHz, 5.47GHz to 5.725GHz, 5.725GHz to 5.850GHz (vary depending on countries)
Max Throughput	1167 Mbps
Service and Management Ports	1 10/100/1000BASE-T Ethernet uplink Port LAN1 supports PoE 1 Console Port (Micro USB)
Power Supply	local power supply (DC 5V/3A) PoE (802.3af)
Power Consumption	<12.95W
Maximum clients per AP	256
Intelligent load balancing based on the number of users or traffic	Support
Bandwidth control	Support
Preference for 5GHz (band select)	Support
PSK, Web, 802.1X authentication	Support
PPSK authentication	Support
IPv4 address	Static IP address or DHCP reservation
IPv6 address	Manual or automatic configuration
Multicast	Multicast to unicast conversion
Network management	SNMP v1/v2C/v3, Telnet, TFTP, Web management
Cloud AC management	Support
FAT/FIT switching	Support
Radio Standard	EN300 328, EN301 893
EMC Standard	GB9254, EN301 489-1, EN301 489-17
Dimensions (W x D x H) (mm)	194 × 194 × 37
Weight	0.42kg
Temperature	Operating Temperature: -10°C to 50°C Storage Temperature: -40°C to 70°C

For enquiries, please contact:



support.cynics.com.my

powered by **Ruijie** NETWORKS