

Professional CCTV Microphone



Powered by **CYNICS**

MIC-C1 : Counter Top / Window Mic

- Range : **10**m², Volume Adjust
- Working Temperature : -25°~70°C
- Casing : PVC, 12VDC
- Dimension : 44(φ) x 10mm, 10g
- Applications : Bank/Service Counter



MIC-W80 : Mini Vandal Resist Mic

- Range : **80**m², Volume Adjust
- Working Temperature : -25°~70°C
- Casing : Aluminum, 12VDC
- Dimension : 30(φ) x 20mm, 23g
- Applications : Prison/Investigation Room, Retail outlet



MIC-W150 : Vandal Resist Mic

- Range : **150**m², Volume Adjust
- Working Temperature : -25°~70°C
- Casing : Aluminum, 12VDC
- Dimension : 82(φ) x 20mm, 158g
- Applications : Prison, Investigation Room



MIC-S100 : Ceiling Mic

- Range : **100**m², Volume Adjust
- Working Temperature : -25°~70°C
- Casing : PVC/Metal Mesh, 12VDC
- Dimension : 30(φ) x 20mm, 23g
- Applications : Bank, Interrogation/Meeting Room



MIC-P300 : Ceiling DNR Mic

- Range : **300**m², Volume Adjust
- Working Temperature : -25°~70°C
- Casing : Alloy/Metal Mesh, 12VDC
- Dimension : 80(φ) x 30mm, 183g
- Applications : Public areas, airport government center etc.



MIC-S150 : Ceiling DNR Mic

- Range : **150**m², Volume Adjust
- Working Temperature : -25°~70°C
- Casing : PVC/Metal Mesh, 12VDC
- Dimension : 80(φ) x 25mm, 79g
- Applications : Conference Room, Office etc.



MIC-PW : Mic. Power

- Working Temperature : -25°~70°C
- Output 12VDC
- Dimension : 90x65x38mm, 235g



* Specification may be changed without prior notice